## **SURFACE EQUIPMENT**

## MINI WINCH | 500m WINCH | 600m WINCH



Robertson Geo designs and builds its own range of winches of varying capacities for deploying subsurface probes on 4-core or co-axial cable.

Each winch is precision engineered for reliable use in the most challenging field applications. The winches are fully compatible with the Micrologger2 surface system and the full range of Robertson Geo probes, for depths of up to 3,000m.

### **Mini Winch**

The Robertson Geo Mini Winch is portable, compact and robust. Its basic 'no-frills' design is aimed at long-term reliability under arduous conditions.

### **SPECIFICATION:**

	Specifications	
	Capacity:	175m (575') 4.72, (3/16") cable
	Speed:	0 – 17.5m/min (0 – 57ft/min) on full drum (12VDC operation)
	Motor:	550W (12 – 24VDC)
	Size:	340(w) x 400(l) x 320(h) mm
	Weight:	19kg excluding cable

## **Part Numbers**

101775.4	AR 1348 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
1013754	Mini Winch includes power and data cables
1001117	Mini Winch Tripod with Encoder



#### 500m Winch

A robust heavy-duty unit, the 500m Winch can be operated from a vehicle battery and is ideal for heavier probes in shallow boreholes.

## **SPECIFICATION:**

	Specifications		
	Capacity:	530m (1738') 3/16" 4-core cable	
	Speed:	0 – 13m/min (0 – 43ft/min)	
	Motor:	180W at 12VDC	
	Size:	582(w) x 482(l) x 414(h) mm	
	Weight:	52kg excluding cable	
_			

# **Part Numbers**

1001019 500m winch including tripod, power and data cable



### 600m Winch


Of similar basic construction to the 500m winch, the 600m is mains/generator powered.

#### SPECIFICATION:

Capacity: 630m (2066') 3/16" 4-core cable   Speed: 0 - 15m/min (0 - 49ft/min)   Motor: 540W at 110/220VAC	Specificat
	Capacity:
Motor: 540W at 110/220VAC	Speed:
	Motor:
Size: 622(w) x 696(l) x 370(h) mm	Size:
Weight: 80kg excluding cable	Weight:

### **Part Numbers**

1001043 600m winch including tripod, power and data cable



Scan the QR code to go directly to www.robertson-geo.com



1/1